

Thermo is a company dedicated to the production of sliding and personnel doors for internal and external applications requiring high standards of hygiene and temperature control.


EXTERNAL DOORS

TDH55/EX


The TDH55/EX external door is designed for use on exterior of buildings with composite insulated panels external facades. The key design features of our external door are:

- Ø Insulation values compatible with the external facades (0.34 W/m2).
- ☑ Due to our flexible fabrication and construction methods, external finish can match exactly that of the external facade.

- Ø Doors are available in 30 or 60 minute fire rating.



SECTION ELEVATION



PLAN

DETAIL A

Threshold detail A where change in floor level is possible. This detail provides best air pressure seal.

DETAIL A

Threshold detail B where floor is level or sloped. This option can include a patent threshold plate if required.

SPECIFICATION

Door leaf

Rebated Leaf

60mm door leaf thickness

Snap in silicone rubber sealing gasket

Finish

Stainless steel with circular polished finish and matt brush finish Plastisol HP200 or PVF2 in a variety of colours

Food Safe laminated steel finish, 0.6mm thickness

Built in frame

Frame clad in the same finish as the door leaf

PVC extruded or PE 500 polycarbonate core

For installation in masonry, wall anchors are providedd

Face fixed frame

Frame clad in the same finish as the door leaf

PVC extruded or PE 500 polycarbonate core

For large doors 10mm fixing bolts and Buffalo T nuts are supplied

Fittings

The door is fitted with stainless steel lever handle

Locking by Euro profile cylinder as standard

Tamper proof stainless steel hinges

Doors can also be fitted with panic bar with or without external access

Options

Double leaf version with 'one active' or 'both active'

Back Frame

Kick Plates

Vision Panel

Variety of ironmongery



- Thermo Ltd, Unit 7, Little Island Industrial Estate, Cork, T45 FH33
- © +353 (0) 21 4354504
- www.thermo.ie
- info@thermo.ie